

Product data			
Product code	Product name	Cable diameter	Cable area
VD03-0001	Cable terminal C-box, C/a, 40-52	40-52 mm	2x(120-185) mm ²
VD03-0002	Cable terminal C-box, C/b, 48-60	48-60 mm	2x(185-300) mm ²
VD03-0003	Cable terminal D-box, D/a, 40-52	40-52 mm	2x(120-185) mm ²
VD03-0004	Cable terminal D-box, D/b, 48-60	48-60 mm	2x(185-300) mm ²
VD03-0005	Cable terminal D2-box, 57-80	57-80 mm	2x(185-300) mm ²

Installation

Type **Screw 4xM8/8.8**

Cable terminal box D/a, C/a (Cable terminal box D/b, C/b)	Cable terminal box D2
<p>Ø 40-42 mm (Ø 48-52 mm)</p> <p>Flip the sleeve inside out</p> <p>Ø 42-52 mm (Ø 50-60 mm)</p> <p>Cut the sleeve from its root</p>	<p>Ø 57-66 mm</p> <p>Let the sleeve be as it was</p> <p>Ø 62-72 mm</p> <p>Pull the sleeve, cut from the halfway and push the rest back in</p> <p>Ø 71-80 mm</p> <p>No sleeve needed during installation</p>

Strip the cable

Pull flange and cone on the cable

Pull the cable through

M = 15-27 Nm

Set the rubber cone and flange correctly, then fasten screws

Note! When installed in hazardous areas and armoured cables are used, strain relief shall be provided close to the cable box (EExe II).