


Five-pole



MAF 25 5P-2

MAF 25 5P-4

MAF 35 5P-2

Light Grey RAL7035	●	MAF5252A32	MAF5254A32	MAF5352A32
--------------------	---	------------	------------	------------

Technical data

Conductor cross-section (per pole)				
Input wire (mm ²)		1 x 10 - 25	1 x 10 - 25	1 x 16 - 35
Output wire (mm ²)		2 x 6 - 16	4 x 6 - 16	2 x 10 - 25
Nominal voltage (V)		400	400	400
Nominal current (A)		80	80	100
Width / Height / Length (mm)		155 / 55,5 / 41,5	155 / 55,5 / 41,5	184,5 / 55,5 / 46,5
Screw		Eccentric screw	Eccentric screw	Eccentric screw
Tightening torque (Nm)		2,5	2,5	2,5 / 3,5
Mounting		DIN rail	DIN rail	DIN rail
Weight (g)		293	437	420
Package (pcs)		1	1	1

Terminal covers

Insulating cover for branching terminals.



MAF Cover 1P25

MAF Cover 4P25

MAF Cover 5P25

MAF Cover 1P35

MAF Cover 4P35

MAF Cover 5P35

Light Grey RAL7035	●	MAF1025A32	MAF4025A32	MAF5025A32	MAF1035A32	MAF4035A32	MAF5035A32
--------------------	---	------------	------------	------------	------------	------------	------------

Technical data

Suitable with	Branch terminals 25mm ²			Branch terminals 35mm ²		
Poles	1	4	5	1	4	5
Material	Rigid PVC	Rigid PVC	Rigid PVC	Rigid PVC	Rigid PVC	Rigid PVC
Weight (g)	3	11	14	4	14	17
Package (pcs)	1	1	1	1	1	1