


Terminals NPE (bridges) can be mounted on DIN rail crosswise. The bridges of the holders are made of highly thermally and mechanically resistant fire-retardant material. These bridges have

IP00 and are intended for location under cover. They are offered in three color variations.



A7, N7, PE7



A9, N9, PE9



A14, N14, PE14

Black	●	MAD0007B00	MAD0009B00	MAD0014B00
Blue	●	MAD0007N00	MAD0009N00	MAD0014N00
Green	●	MAD0007G00	MAD0009G00	MAD0014G00

Technical data


Conductor cross section CU (mm ²)	1,5 - 16	1,5 - 16	1,5 - 16
Nominal voltage (V)	690	690	690
Nominal current (A)	63	63	63
The number of connection points	7	9	14
Tightening torque (Nm)	2,5	2,5	2,5
Width / Height / Length (mm)	13 / 30 / 60	13 / 30 / 61	13 / 30 / 94
Mounting	Din rail	Din rail	Din rail
Weight (g)	28	32	48
Package (pcs)	20	20	20

Terminals NPE (bridges) can be mounted on DIN rail crosswise. The bridges of the holders are made of highly thermally and mechanically resistant fire-retardant material.

These bridges have IP20 protection class. They are offered in three color variations.



**A7H,
N7H, PE7H**



**A12H,
N12H, PE12H**



**A15H,
N15H, PE15H**



**A6H-2,
N6H-2, PE6H-2**

Grey	●	MAD1007A15	MAD1012A15	MAD1015A15	MAD2006A15
Blue	●	MAD1007N15	MAD1012N15	MAD1015N15	MAD2006N15
Green	●	MAD1007G15	MAD1012G15	MAD1015G15	MAD2006G15

Technical data

Conductor cross section CU (mm ²)	1,5 - 16	1,5 - 16	1,5 - 16	8 x 2,5 - 16 4 x 4 - 25
Nominal voltage (V)	690	690	690	500
Nominal current (A)	63	63	63	63
The number of connection points	7	12	15	2 x 6
Tightening torque (Nm)	2	2	2	2
Width / Height / Length (mm)	13 / 27 / 53	13 / 27 / 87	13 / 27 / 106	30 / 27 / 53
Mounting	DIN rail	DIN rail	DIN rail	DIN rail
Weight (g)	28	45	57	88
Package (pcs)	10	10	10	10